GS T59 INDUSTRIAL MOBILE COMPUTER





FEATURES

High-Speed 5G Connectivity&Performance

Powered by a 2.4GHz octa-core processor, the T59 supports 5G/4G full-band communicatin with VoLTE HD calls. Integrated Wi-Fi 6E enables up to 2x faster data transfer, while Bluetooth 5.2 ensures stable, low power connectivity.

· Zebra SE4770 Scan Engine - Fast, Accurate, and Reliable

T59 is equipped with the Zebra SE4770 scan engine. With maximum motion tolerance and high first-pass read rates, it enables workers to capture barcodes instantly - even when either the device or the barcode is moving. Its wide scanning range and enlarged "sweet spot" minimizes the need for manual adjustment and boosting operational efficiency.

8GB+128GB - Powerful Memory for Seamless Performance

With 8GB of RAM and 128GB of internal storage, T59 delivers faster response times, smoother multitasking, and ample space for industrial applications and data storage. Whether running complex warehouse management systems, processing large databases, or handling real-time communication, it ensures stable and efficient performance without lag.

• 6.0-inch HD+ Screen with Industrial-Grade Protection

T59 is equipped with a 6.0-inch HD+ display offering an exceptional 95% screen-to-body ratio for an immersive visual experience. With 1.5-meter drop resistance and IP68-rated dust and water protection, the T59 is built for superior durability in challenging environments.

PRODUCT SPEC SHEET

GS T59 MOBILE COMPUTER

PHYSICAL PARAMETER

| Dimensions | 163.3mm(L)×77.4mm(W)×13.8mm(D) | |
|--------------|--|--|
| | 6.43in.(L)x3.05in.(W)×0.54in.(D) | |
| Weight | 268g/9.45oz.(includes battery) | |
| Keypad | Virtual Keypad - Menu, Home, Return | |
| | Physical Keypad - Left/Right Scan Key, power key, volume key | |
| Notification | Vibration/LED/Audio | |

PLATFORM AND FEATURES

| Operating System | Android 15.0 with GMS | |
|---------------------|---|--|
| CPU | Qualcomm 4490(2*A78+6*A55), up to 2.4GHz | |
| Display | 6", HD+, 720×1440 | |
| Touch Panel | GFF 10-point control, glove operation and wet hand | |
| | operation available | |
| Memory Type | 8GB RAM+128GB ROM | |
| SIM | Nano SIM slot×2 | |
| Extended Storage | Micro SD Card, up to 128GB, SDHC | |
| Camera | Front camera 5M, rear camera 13M, PDAF Quick Focus+ | |
| | Night Shot Light(optional higher) | |
| Battery | 5000mAh, removable | |
| Battery Fast Charge | 9V/2A | |
| Network Connections | USB Type-C, OTG | |
| Motion Sensors | Optical Distance Sensor/Gravity Sensor/Gyroscope/ | |
| | Geomagnetic Sensor/Air Pressure Sensor | |
| | | |

NFC SPECIFICATION

| Frequency | 13.56MHz |
|------------------|---|
| Reading Distance | The farthest card reading distance is 2cm |
| Protocol | ISO 14443 A |
| | ISO 14443B |
| | |

RF SPECIFICATION

| BT 5.2 |
|---|
| IEEE 802.11a/b/g/n/ac/ax |
| GSM 850/1900 |
| WCDMA B2/4/5 |
| LTE_TDD B38/41/48 |
| LTE_FDD B2/4/5/7/8/12/13/14/17/25/29/30/66/71 |
| NR_TDD n38/41/48/77/78 |
| NR_FDD n2/5/7/12/13/14/25/26/29/30/66/70/71 |
| GSM/CDMA/CDMA-EVDO/TD-SCDMA/WCDMA/TDD LTE/ |
| FDD LTE/5G |
| GPS L1/L5, GLO G1, BDS B1I/B1C/B2A, QZSS |
| |

PERFORMANCE CHARACTERISTICS

| Optical Resolution | 1280×800 pixels/844×640 pixes | |
|--------------------------|--|--|
| Scan Angles | Pitch +/-45° | |
| | Roll (Tilt) 360° | |
| | Skew(Yaw) +/-60° | |
| Scan Accuracy | ≥3mil , Code 39/128 | |
| Illumination Element | White LED | |
| Aiming Element | Red Cross Laser(650nm) | |
| Symbol Decode Capability | 1D: Codabar, Code 11, Code 128, Code 39, Code93, | |
| | EAN8, EAN13, GS1 128, Matrix 2 or 5, Trioptic, IATA25, | |
| | INT25, MSI, STRT25, Telepen, UPC-A, UPC-E0, UPC-E1, | |
| | NEC25, USPS4CB, HK25 | |
| | 2D: Aztec Code, Grid Matrix, Data Matrix, HanXin Code, | |
| | Maxicode, MicroPDF, PDF417, QR, RSS, RSL, RSE, | |
| | Codablock A, Codablock F | |

DECODE RANGES

| 7.5 mil Code 39 | 3.15in9.061in. / 80mm-230mm |
|--------------------|-------------------------------|
| 9.2 mil Code39 | 2.76in10.24in. / 70mm-260mm |
| 10 mil Data Matrix | 5.12in6.30in. / 130mm-160mm |
| 12.5 mil Code128 | 1.97in17.32in. / 50mm-440mm |
| 20 mil QR Code | 2.36in23.82in. / 60mm-605mm |
| 25 mil Code128 | 6.30in54.33in. / 160mm-1380mm |

USER ENVIRONMENT

| Operating Temperature | -4°F~140°F/-20°C~60°C |
|-----------------------|---|
| Storage Temperature | -40°F~140°F/-40°C~60°C |
| Humidity | 0%-95%,non-condensing |
| Drop Spec. | Survive from 4.92 ft. / 1.5m multiple drops |
| IP Level | IP 68 |
| ESD | ±8kv contact discharge; ±12kv air discharge |

SOFTWARE SUPPORT

| Generalscan Keyboard Pro | |
|--------------------------|--|
| Generalscan SDK Demo | |
| Generalscan OTA Tools | |
| G-Service | |

OPTIONAL ACCESSORIES

USB Type-C Cable, Adaptor, Hand Strap, Protective Case, Resource Download Card

GENERALSCAN

+17323917747 🕲

+90 542 478 5873 🕓

+17323917747

sales@generalscan.cloud

